



TORQUES PARA BONETES CAMERON de BOP's tipo: U, UL y UM

CALIBRE Y PRESIÓN DE TRABAJO	DIÁMETRO BIRLO 8UN	HEX BONETE ACROSS FLAT	TORQUE EN LBF-FT (MOLY LUB)	LLAVES HYTORC SERIES STEALTH	PRESIÓN EN BOMBA (PSI)
7-1/16" 3,000	1-3/4"	2-3/8"	711	Stealth-4	1,800
7-1/16" 5,000	2"	2-3/8"	1,123	Stealth-4	2,800
7-1/16" 10,000	2-1/2"	2-3/4"	2,603	Stealth-8	3,300
7-1/16" 15,000	2-7/8"	2-3/4"	4,011	Stealth-8	5,000
11" 3,000	2-1/4"	2-3/4"	1,923	Stealth-8	2,400
11" 5,000	2-1/2"	2-3/4"	2,603	Stealth-8	3,300
11" 10,000	3-1/8"	2-3/4"	5,013	Stealth-8	6,200
11" 15,000	3-3/4"	3-1/2"	8,982	Stealth-14	6,200
13-5/8" 3,000	2-3/4"	2-3/4"	3,548	Stealth-8	4,400
13-5/8" 5,000	2-7/8"	2-3/4"	4,011	Stealth-8	5,000
13-5/8" 10,000	3-3/4"	3-1/2"	8,982	Stealth-14	6,200
13-5/8" 15,000	4-1/2"	4-5/8"	15,758	Stealth-36	4,500
16-3/4" 3,000	2-7/8"	3-1/2"	4,011	Stealth-8	5,000
16-3/4" 5,000	3-1/2"	3-1/2"	7,331	Stealth-14	5,200
16-3/4" 10,000	4-1/2"	4-5/8"	15,758	Stealth-36	4,500
18-3/4" 10,000	4-3/4"	4-5/8"	18,415	Stealth-36	5,200
20-3/4" 3,000	2-1/2"	2-3/8"	2,603	Stealth-8	3,300
21-1/4" 2,000	2-1/4"	2-3/4"	1,913	Stealth-8	2,400
21-1/4" 5,000	4-3/4"	4-5/8"	18,415	Stealth-36	5,200
21-1/4" 7,500	5"	4-5/8"	21,191	Stealth-36	6,000
21-1/4" 10,000	5"	4-5/8"	21,191	Stealth-36	6,000
26-3/4" 2,000	2-1/2"	2-3/8"	2,603	Stealth-8	3,300
26-3/4" 3,000	3-3/4"	3-1/2"	8,982	Stealth-14	6,200

Torques recomendados por Cameron utilizando lubricante tipo Moly en las roscas.

[www.hytorcdemexico.com.mx](http://www.hytorcdemexico.com.mx)