



MEDIDAS DE CABEZALES DE VÁLVULAS API Y BOP'S

CALIBRE DE PRESIÓN DE TRABAJO							A.F. TAMAÑO TUERCA	DIÁMETRO TORNILLO	TORQUE SUGERIDO (lb _r -ft)	LLAVE HYTORC	PRESIÓN BOMBA (PSI)
2M	3M	5M	7.5M	10M	15M	20M					
2-1/16							1-1/16"	5/8"	250	HY-2XLCT	1500
2-9/16 3-1/8				1-13/16	2-1/16		1-1/4"	3/4"	300	HY-2XLCT	1800
4-1/16	3-1/8	2-1/16		2-9/16	1-13/16		1-7/16"	7/8"	450	HY-2XLCT	2600
1-13/16 5-1/8 7-1/16		2-9/16		3-1/16	2-9/16		1-5/8"	1"	550	HY-2XLCT	3200
2-1/16 9	4-1/16 7-1/16	3-1/8		4-1/16 5-1/8	3-1/16		1-13/16"	1-1/8"	800	HY-2XLCT	4800
2-9/16 11 13-5/8	5-1/8	4-1/16					2"	1-1/4"	1000	HY-2XLCT	5800
11 3-1/16	13-5/8	7-1/16			4-1/16		2-3/16"	1-3/8"	1200	HY-2XLCT HY-4XLCT	7000 3200
16-3/4		5-1/8		7-1/16 9	7-1/16		2-3/8"	1-1/2"	1400	HY-2XLCT HY-4XLCT	8200 3600
21-1/4	16-3/4	13-5/8 9					2-9/16"	1-5/8"	1700	HY-2XLCT HY-4XLCT HY-8XLCT	9900 4400 2200
4-1/16				11		4-1/16	2-3/4"	1-3/4"	2100	HY-4XLCT HY-8XLCT	5500 2600
		16-3/4 11		16-3/4 13-5/8	9		2-15/16"	1-7/8"	3220	HY-4XLCT HY-8XLCT	8400 4100
7-1/16	20-3/4	18-3/4 21-1/4			11		3-1/8"	2"	3850	HY-4XLCT HY-8XLCT	9900 5000
	9						3-3/16"	1-3/8"	1200	HY-2XLCT HY-4XLCT	7000 3200
				18-3/4	13-5/8		3-1/2"	2-1/4"	4150	HY-4XLCT HY-8XLCT	9400 5400
			21-1/4	21-1/4			3-7/8"	2-1/2"	5100	HY-8XLCT	6700
					18-3/4		4-5/8"	3"	11300	HY-14XLCT	8500